

# PRODUCT DATA SHEET HF6R Work (C91)





2 - PRODUCT DATA SHEET V230329

### HF6R Work

#### PRODUCT DESCRIPTION

The Ledlenser HF6R Work is our slim headlamp for regular industrial and trade applications. It comes with a high-quality aluminum housing, three brightness levels and a red front light. Apart from that, the HF6R Work is equipped with a high color rendering index for close-range work. Thanks to our patent-pending Digital Advanced Focus System, the HF6R Work allows virtually seamless focusing. The digital AFS can be used intuitively via Focus Wheel. Protective elements at the front prepare the lamp for demanding applications – thanks to its powerful battery, you can use the HF6R Work for up to eight hours at mid-intensity. Other features include the wall holder as well as various mounting options on helmets.

- Slim, rechargeable headlamp with three brightness levels as well as red front light
- Virtually seamless focusing thanks to our patent-pending Digital Advanced Focus System; intuitive-to-use Focus Wheel
- Protective elements at the front for high impact resistance; suitable for continuous immersion in water (IP68)
- Powerful battery; easily rechargeable via Magnetic Charge System, with battery status indicator
- Flexible thanks to rubberized headband and additional helmet mount and wall holder

TECHNICAL DATA	
Weight incl. batteries [g]	134
Focus function	Yes (digital)
Head material	Aluminum alloy + PC
Tube material	Aluminum alloy + PC
Optic	Plastic lense (PMMA)
Headband material	Elastic fabric
Headband type	Side headband
Head movement type	Stepless movement
Head movement angle [°]	45
Headband specifications	Detachable,
	Elastic,
	Rubberised back,
	Washable

Rechargeable battery
1
Li-ion
No
3.7
2000
7.4
Yes
225
Battery Indicator,
Charge Indicator,
Low Battery Warning

FURTHER SPECIFICATIONS		
IP class	IP68	
Drop test (drop height) [m]	2	
Working temperature range [°C]	-20 to +40	

#### LIGHT FUNCTIONS

Boost, Power, Mid Power, Low Power

LIGHT SOURCE	
Amount LEDs	3
LED type	Xtreme LED
Color	White
Color temperature [K]	4600 to 5400
Color rendering index (CRI)	80

LIGHT VALUES				
	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]	800	500	200	20
Beam distance <sup>1</sup> [m]	160	140	80	25
Run time <sup>1</sup> [h]		3	8	60

#### **SWITCH**

Front Switch, Rotary Switch

#### **FEATURES**

Red Light, Memory Function, Transportation lock, Backup Mode

#### TECHNOLOGIES

Temperature Control System, Magnetic Charge System, Digital Advanced Focus System, Cooling Technology



4 - PRODUCT DATA SHEET V230329

## HF6R Work

### **ACCESORIES**

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME
Fastenings / Brackets	503003	Wall Mount Type D
Fastenings / Brackets	502254	Helmet Mount for Euroslot Type A
Fastenings / Brackets	502256	Universal Mounting Bracket Type E
Fastenings / Brackets	502314	Helmet Connecting Kit Type H
Pouches / Holster	0332	Pouch Type H
Charger / Cable	502265	Magnetic Charging Cable Type A
Charger / Cable	502929	USB-C Adapter 20W

