

PRODUCT DATA SHEET P17R Core (C33)





2 - PRODUCT DATA SHEET V201116

P17R Core

PRODUCT DESCRIPTION

The P17R Core is an extremely reliable and bright flashlight. It is ergonomically-friendly and can be easily operated with the Fast Action Switch, making it security officer's favorite tool. The patented³ Advanced Focus System provides a continuous transition from a broad flood beam to a sharply focused long-distance beam. The energy for this extremely durable flashlight is provided by a rechargeable Safety Ytrion Cell, one of the safest and most durable rechargeable battery cells on the market.

- Advanced Focus System for efficient, precise flood and spot lighting
- Smart Light Technology for custom light functions
- Constant Light for constant luminous flux over a long period of time
- Convenient charging of the battery with wall mount and Magnetic Charge System
- Fast Action Switch for easy operation of the light functions

TECHNICAL DATA				
Length defocused [mm]	290			
Length focused [mm]	300			
Head diameter [mm]	53			
Tube diameter [mm]	40			
Weight incl. batteries [g]	715			
Weight without batteries [g]	400			
Focus function	Yes			
Head material	Aluminum alloy			
Tube material	Aluminum alloy			
Optic	Plastic lense (PMMA)			
Cartridge	No			

POWER SUPPLY				
Power source type	Rechargeable battery			
Battery quantity	1			
Battery type	LiFeP04			
Total battery voltage [V]	6.4			
Total battery capacity [mAh]	5700			
Total battery energy ² [Wh]	36.48			
Rechargeable	Yes			
Charging time ⁵ [min]	270			
Energy modes	Constant Light			
Energy status indicator	Battery Indicator,			
	Charge Indicator,			
	Low Battery Warning			

FURTHER SPECIFICATIONS				
IP class	IP54			
Drop test (drop height) [m]	1			
Working temperature range [°C]	-20 to +40			

LIGHT FUNCTIONS

Blink, Boost, Low Power, Mid Power, Power, Position, S.O.S., Strobe

LIGHT SOURCE			
Amount LEDs	1		
LED type	Xtreme LED		
Color	White		
Color temperature [K]	6000 to 7500		
Color rendering index (CRI)	65		

LIGHT VALUES	5			
ANSI – Constant Light	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	1200	900	350	15
Beam distance ¹ [m]	560	420	270	50
Run time ¹ [h]		2.75	12	200

SWITCH

Front Switch, Mode Switch

FEATURES

 $\label{limball} \mbox{Dimmable , Transportation lock , Focus lock , Flicker Free, Memory Function, Back-Up Light}$

TECHNOLOGIES

Advanced Focus System³, Rapid Focus, Smart Light Technology, Temperature Control System, Emergency Light, Magnetic Charge System, Safety Ytrion Cell

